



# SPEAR TOP FENCING

## OUR PROCESS:

1. Contact us to discuss your scope and timeframes.
2. A quote and drawings will be prepared & once accepted the job will be booked in.
3. Installation begins. You will be updated on progress and expected finish date.
4. Project is completed and site is cleaned & in working order.

When security is important, we often install heavy duty steel security fencing.

This fencing system uses square posts and typically 2400mm wide panels fixed between the posts using anti-tamper screws

## PANEL SIZES

| Width  | Height   |                 |
|--------|----------|-----------------|
| 2400mm | 1800mm   | Standard        |
| 2400mm | 2100mm   | Standard        |
| 2400mm | 2400mm   | Standard        |
| 2400mm | > 2400mm | Made to measure |

- Horizontal rails: 40mm x 40mm.
- Vertical pickets: 25mm x 25mm.
- Finish: Powdercoated Black.
- Top of Pickets: Spear top or Square.
- Picket spacings: 140mm centres for standard panels. Department of Education Spec is 125mm centres or 115mm for Prep Spec DoE fences.

## POST OPTIONS

| Post Size (SHS) | Application    |
|-----------------|----------------|
| 65mm x 65mm     | Fence          |
| 75mm x 75mm     | Fence          |
| 100mm x 100mm   | Standard Gates |
| 125mm x 125mm   | Heavy Gates    |
| 150mm x 150mm   | Heavy Gates    |

## FOOTINGS

- Fence posts: 700mm in ground.
- Gate posts: 700mm to 1000mm in ground depending on gate size.

## SPEAR TOP SECURITY FENCING



2100mm high steel security fencing  
for a High School



Single 1800mm high security  
gate with mesh



Raked security panels installed on concrete retaining wall.

## CONTACT



0480 462 426



[projects@woodtrades.com.au](mailto:projects@woodtrades.com.au)



[www.woodtrades.com.au](http://www.woodtrades.com.au)



9 metre sliding gate

**COMMERCIAL • INDUSTRIAL •  
PUBLIC INFRASTRUCTURE**