



SCHOOL FENCING

OUR PROCESS:

1. Contact us to discuss your scope and timeframes.
2. A quote and drawings will be prepared & once accepted the job will be booked in.
3. Installation begins. You will be updated on progress and expected finish date.
4. Project is completed and site is cleaned & in working order.

All of our contractors have Blue Cards and can present these upon arrival at your school.

DoE SPEC - Spear Top

We supply and install DETE spec fencing, which means it complies with the Education Queensland Departments specifications.

COMMON FENCING CONFIGURATIONS

- 2.1 metre high black spear top security fences and gates,
- 1.8 metre or 2.1 metre Chainwire fences and gates,
- 1.2 metre high aluminium or steel fences and gates.
- We also install Chainwire, Aluminium and Colorbond Fencing based on individual requirements.
- The gates are either swinging or sliding, & can be installed with or without a motor.

Spear Top Type	Spacing between pickets	Coating	Uses
DoE Spec Fence	100mm gap (125mm centres)	Power coated galvanised steel construction with Z275 coating. This zinc coating reduces corrosion over the long term and is specced for State Government fence.	Most popular in Schools.
Prep Spec Fence	90mm gap (115mm centres)		Most popular in Kindergartens.
Standard Security Fence	115mm gap (140mm centres)	Powder Coated Galvanised Steel Construction.	Unlikely to use in a School setting.



PREP Spec Stepped Fencing



DETE Spec Fencing on a Retaining Wall



Sports Court Chainwire Fencing

CONTACT



0480 462 426



projects@woodtrades.com.au



www.woodtrades.com.au



1200mm high Aluminium Fencing for a drop off zone